Eminence™ Lighted Wardrobe Mirror

Product Specifications: Residential

ELECTRIC MIRROR®



PRODUCT DESCRIPTION

The Eminence™ lighted wardrobe mirror has been embraced by designers for the prestige and distinction it brings to any room it graces. Its unique shadow-box frame, inward-facing task lighting, and ambient wall-glow seamlessly combine to achieve the perfect balance of form and function.

SPECIFICATION STATEMENT

Solution shall consist of a lighted wardrobe-length mirror with integrated one-touch dimming. LEDs will be mounted in a 90-degree channel in the frame of the mirror, with inward-facing directional lighting on the front face of the mirror and ambient glow behind the mirror. LEDs shall have an L_{70} life of >54,000 hours, with a greater than or equal to 90 CRI (color rendering index) and will be covered by an integrated diffuser. Product shall incorporate a driver enclosure that is to be mounted to the back of the mirror. Product will have a 7-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 25 years
- oxdot More installations than all competitors combined
- Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S.-based customer service and support
- ☑ 125,000-square-foot American manufacturing facility

FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant OmegaMirror™
- One-touch dimmable inward-facing task lighting for brilliant facial illumination
- One-touch dimmable wall-glow ambient lighting with diffuser for a finished side view
- Greater illuminance with half the power consumption of traditional LED mirrors
- Sleek and modern profile
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Easy installation
- JA8-2022 compliant
- 7-year limited warranty
- Patent: <u>www.electricmirror.com/patents</u>
- Designed in the USA

FINISHES



LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000K
- 351 initial lumens/foot (front lighting)
- 713 initial lumens/foot (wall-glow)
- Maximum 98 lumens/watt efficacy
- Reported L₇₀ >54,000-hour LED lifespan
- Built-in EMX diffusers

SAFETY & INSTALLATION SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- Safety-backed mirror
- 120VAC hardwire electrical connection; whip provided with mirror; junction box controlled by a wall switch (by others) is required
- Fixture should be mounted to wall studs; wall cleat provided
- Controlled by non-dimming wall switch for on/off, and capacitive touch button on fixture for dimming
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Model Number	Finish	Dimensions	Initial Lumens/Fixture	Power Requirements
EMN-2660-BK05 EMN-2660-BR02	Matte Black (BK-05) Brushed Brass (BR-02)	26" W x 60" H x 2.76" D (660mm W x 1,524mm H x 70mm D)	13,650	120VAC, 124W

DIMENSIONAL DRAWING (Not to scale.)

