




PRODUCT DESCRIPTION

Eternity™ unites a romantic shape with a stunning circle of brilliant light that encapsulates a clear vision of renewal and balance, boldly illuminating your space with timeless elegance.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting and 480-hour CASS-tested, lead-free, copper-free, corrosion-resistant glass. Mirror shall have uniform light output in frosted areas, using high-density (54 LEDs/foot) dimmable, replaceable LED strips with 90+ CRI (Color Rendering Index) and delivering 1,280 initial lumens/foot with an efficacy of 140 lumens/watt. Product will be made in America with U.S. and global components and have a 7-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ✓ Global mirror technology leader for over 25 years
- ✓ More installations than all competitors combined
- ✓ Realistic warranty you can believe in and trust
- ✓ Lowest total cost of ownership
- ✓ U.S.-based customer service support
- ✓ 125,000-square-foot American manufacturing facility

LIGHTING FEATURES AND BENEFITS

- Industry-leading lumen output for better task lighting
- Superior color rendering (CRI) for more natural, flattering, and softer light quality
- High-density linear LED design for even light distribution
- High-efficiency LEDs for best-in-class energy savings
- Forward-facing task lighting for ideal makeup application and grooming
- Forward-phase/triac dimming technology

GENERAL FEATURES AND BENEFITS

- OmegaMirror™ corrosion-resistant, 480-hour CASS-tested proprietary mirror glass
- Environmentally-leading, lead-free, copper-free mirror glass composition
- Fast lead times
- Easy installation
- Title 24 compliant
- JA8-2022 compliant
- 7-year limited warranty
- Patent: www.electricmirror.com/patents
- Made in America with U.S. and global components

AVAILABLE OPTIONS


- [Ava™ touch-tunable white + dimming technology](#)¹
- Defogger
- Custom sizes

LIGHTING SPECIFICATIONS

- Best-in-class illumination: 1,280 initial lumens/foot
- Superior color rendering: 90+ CRI
- High-density design: 54 LEDs/foot
- High efficacy: 140 lumens/watt
- Color temperature (CCT): 3,000K
- LED L₇₀ Lifespan: 52,000-hours
- Extended longevity: replaceable LEDs

¹ See technology specification sheets for more details

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)



MODELS

Base Model*	Model Type	Dimensions	Initial Lumens/Fixture	Power Requirements
ETE-2130	Standard	21" W x 30" H x 1.75" D	6,614	120VAC, 51W
ETE-2130-AK	With Ava™	(533mm W x 762mm H x 44mm D)	2,753	120 or 277VAC, 36W
ETE-30	Standard	30" DIA x 1.75" D	7,681	120VAC, 59W
ETE-30-AK	With Ava™	(762mm DIA x 44mm D)	3,197	120 or 277VAC, 42W
ETE-36	Standard	36" DIA x 1.75" D	10,241	120VAC, 78W
ETE-36-AK	With Ava™	(914mm DIA x 44mm D)	4,262	120 or 277VAC, 56W

*Base model number shown only. To specify additional options, contact Electric Mirror at residential@electricmirror.com.

SAFETY & INSTALLATION SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror
- 120VAC hardwire electrical connection; provide whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Controlled by forward-phase dimming wall switch (by others)
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable